

Data sheets

eco Display 210 FR + w

Article number: 4280/26eco
Material: 100 % PES
Weight: ca. 210 g/m²

Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Specialities:

crease resistant
elastic ca. 2-3%
not transparent for frame systems
heat set ca. 195°C (> 195°C shrinkage ca. 1%)
no fraying

Applications:

soft signage / Pop up display systems
X-Kite Display Systems
banners
roll up display systems
display frame systems
Textile wallpaper

Remarks:

Stretch: ca. 1-2 % length direction, ca. 2-3 % width and diagonal direction

the perfect allroundtextil for dyesubdirectprinter like Aquajet (Gandi), Artistri (Dupont), Teleios (Dgen), etc.

* special size for HP Latex printers

Product compatibilities:

eco Display 210 FR + w is compabtible to the following printers (print-method):

Vutek FabriVu (Sub Oil)	D-Gen Teleios (Sub water)
Gandi Jeti 3312 DS (Sub Oil)	Vutek QS Series (UV curable)
Durst Rho 160/350 (UV curable)	Dupont Artistri (Sub water)
Mimaki JV 4 / TX2 sub direct (Sub water)	HP Expedio 3200 / 5000 (UV curable)
Paper Transfer (Sub Paper)	Spühl Virtu (UV curable)
Gandi Aquajet (sub water)	ATP Color/Roland (Sub water)
Hollanders Colorbooster (Sub water)	Mimaki DS series (Sub water)
Mutoh Viper (Sub water)	Roland FP 740 (Sub water)